


Rugged i9000S Smart POS Payment Terminal



Multiple Payment Solutions

MSR, Chip card, NFC
2D payment
Membership rewards point

Powerful Data Collection

5MP camera
GPS positioning

Advance Capacitive Touchscreen

5" HD(1280 × 720)
Industrial grade sensitivity,
works with gloves and wet fingers.

Optional Finger Module

Thermal Printer

2" thermal printer
40mm paper roll
Supports 2D barcode printing



Finger print

SPECIFICATIONS

Basic Characteristics

O.S.	Safedroid OS (based on Android 8.1), supports multi-language
CPU	Quad-Core 1.1GHz
Display	5.0 inch TFT-LCD HD (720 x 1280) color screen
Panel	Ultra sensitive capacitive touch screen, works with gloves and wet fingers
RAM	1GB
ROM	8GB
Dimensions	184mm x 81 mm x 32mm (max 51mm)
Weight	490g (Battery included)
Buttons	Front: Meun key x 1, Home key x 1, Return key x 1, User definable button x 1, Cancel button x 1, Confirm button x 1, Clear button x 1 Side: The volume switch button, Power button
Input	Supports handwriting and soft keyboard

Radio Communication

Wi-Fi	802.11 b/g/n wireless communication
Bluetooth	Bluetooth 4.1 + BR/EDR +BLE
Radio Communication	4G TDD-LTE: B40 FDD-FTE: B1/B2/B3/B4/B5/B7/B8/B20
	3G WCDMA(B1/B2/B5/B8)
	2G GSM/EDGE/GPRS/CDMA: 850/900 /1800/1900MHz

Power

Main Battery	Rechargeable 3.8V, 5000mAh lithium polymer battery pack (Typical Operation time ≥8 hours)
RTC Battery	Real time clock battery

Payment

Magcard	Supports ISO7811/7812/7813, and supports triple track (tracks 1/ 2/ 3), bi-directional
Chip Card	Supports ISO7816 standard
Contactless Cards	Supports 15693; Supports 14443A / 14443B; Supports 10MHz~20MHz frequency, and reading time less than 300 milliseconds
Printer	58mm printing paper, 203dpi / 8dot / mm; Printing speed: 50~70mm/s, and supports barcode printing, 40mm media roll size

Expansion and Peripherals

Camera	5MP camera with LED flash and auto-focus function
GPS	GPS, Supports A-GPS, GLONASS, Beidou
Slot	Micro SD/TF x 1(a maximum of 128 GB), SIM x 1,
PSAM	SAM x 2 Conforms to ISO7816 standard
Interfaces	Micro USB x 1, Pogo pin x 1, 3.5mm Audio Jack x 1, DC Jack
Audio Frequency	Speaker

Accessories

Standard	Power adaptor, Data line, One battery.
Optional	Dual-Slot Battery Charger, Carrying Pouch, Cradle, Hand Strap, Stylus, Media roll.

User Environment

Operating Temperature	-20~50 °C (-4~122°F)
Storage Temperature	-40~70 °C (-40~158°F)
Humidity	5% ~ 95% (non condensing)
Drop Durability	1.3m

Product Certification

Certification	CCC, CE, FCC, RoHS, PCI, EMV LEVEL 1&2, EMV Contactless LEVEL 1 certification, PayWave, PayPass, American Express Expresspay
---------------	--

Accessories

